

## polo tall compact grade product summary



### Features:

Visible powder coated full aluminium frame.

Framework available in two colours, dark and light grey.

Full height up to 2400mm with 28mm floor gap.

Also available at a standard height of 2000mm with a 150mm floor gap.

Finished door thickness of 12mm.

Anti-fingertrap feature.

Rise and fall self-closing door mechanism located in foot.

Pivoted door.

Powder coated aluminium fittings.

Machined painted aluminium lock locates into post.

Wide range of compact grade laminates available, from various leading manufacturers.

Emergency release.

10 year warranty.

Also available in:

● HPL



**thrislington cubicles**

t +44 1244 520 677  
e [info@thrislingtoncubicles.com](mailto:info@thrislingtoncubicles.com)  
[www.thrislingtoncubicles.com](http://www.thrislingtoncubicles.com)

**Warranty:** 10 Years.

**Tested:** 200,000 operations.

**Made in the UK**



**thrislington cubicles**

t +44 1244 520 677  
e info@thrislingtoncubicles.com  
www.thrislingtoncubicles.com

### **K32 Specification: Polo Tall Compact Grade Cubicles**

**Specification:** Overall cubicle height up to 2400mm with 28mm floor clearance, supplied with a 10 year warranty.

**Framework:** Full aluminium frame in specified colour using Aluminium Alloy 6063T6 having a polyester powder coated finish and with 60% recycled content, including extruded aluminium headrail and vertical posts. Lock locates directly into vertical closing post, including buffers.

**Door:** 12mm compact grade laminate, polished to all visible edges. Extruded full length powder coated aluminium channel, allows the door to pivot between a structural aluminium headrail and floor fixed pivot bracket. Floor bracket incorporates a rise and fall closing mechanism. Complete with anti-finger trap clearance on pivot side of door.

**Divider:** 12mm compact grade laminate, polished to all visible edges. Suspended 28mm from the floor using extruded aluminium bracket to the back wall.

**Fascia:** Where required, 12mm compact grade laminate, polished to all visible edges. Suspended 4mm from the floor.

**Fittings:** Painted aluminium lock, hand-turned in UK and able to be opened with a closed fist, is fixed through the door to the face plate for added strength. Sacrificial hard nylon shear tip to the lock finger, which locates directly into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using extruded powder coated aluminium brackets secured using through-fixings. Powder coated aluminium coat hook supplied as standard. Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

#### **Finishes:**

**Aluminium:** Powder coated dark grey (RAL 7011) or light grey (RAL 7035).

**Door:** 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

**Divider:** 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

**Fascia:** 12mm compact grade laminate from our standard ranges, which include various leading manufacturers.

