

polo tall laminate product summary



Features:

Visible powder coated full aluminium frame.

Framework available in two colours, dark and light grey.

Full height up to 2400mm with 28mm floor gap.

Also available at a standard height of 2000mm with a 150mm floor gap.

Finished door thickness of 19mm.

Anti-fingertrap feature.

Rise and fall self-closing door mechanism located in foot.

Pivoted door.

Powder coated aluminium fittings.

Machined painted aluminium lock locates into post.

Wide range of laminates available, from various leading manufacturers.

Core sourced from legal and sustainable sources. Can be supplied to meet NAUF criteria.

Emergency release.

10 year warranty.

Also available in:

● GCL



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

Warranty: 10 Years.

Tested: 200,000 operations.

Made in the UK



thrislington cubicles

t +44 1244 520 677
e info@thrislingtoncubicles.com
www.thrislingtoncubicles.com

K32 Specification: Polo Tall Laminate Cubicles

Specification: Overall cubicle height up to 2400mm with 28mm floor clearance, supplied with a 10 year warranty.

Framework: Full aluminium frame in specified colour using Aluminium Alloy 6063T6 having a polyester powder coated finish and with 60% recycled content, including extruded aluminium headrail and vertical posts. Lock locates directly into vertical closing post, including buffers.

Door: 19mm finished thickness consisting of 17mm moisture resistant chipboard core using timber from sustainable forests, faced with high pressure laminate and edged all round with 2mm PVC/ABS tape to match framework finish. Extruded through-fixed aluminium brackets allow the door to pivot between a structural aluminium headrail and floor fixed foot. Foot incorporates a rise and fall closing mechanism and includes height adjustment. Complete with anti-finger trap clearance on pivot side of door.

Divider: 19mm finished thickness consisting of 17mm moisture resistant chipboard core sourced from sustainable forests, faced with high pressure laminate and finished to all visible edges with 2mm PVC/ABS tape to match framework finish. Suspended 28mm from the floor using extruded aluminium bracket to the back wall.

Fascia: Where required, 19mm finished thickness consisting of 17mm moisture resistant chipboard core sourced from sustainable forests, faced with high pressure laminate and finished to all visible edges with 2mm PVC/ABS tape to match framework finish. Suspended 4mm from the floor.

Fittings: Painted aluminium lock, hand-turned in UK and able to be opened with a closed fist, is fixed through the door to the face plate for added strength. Sacrificial hard nylon shear tip to the lock finger, which locates directly into the vertical closing post. Complete with emergency release facility. Divider fixed to back wall using extruded powder coated aluminium brackets secured using through-fixings. Powder coated aluminium coat hook supplied as standard. Components tested over a cycle of 200,000 operations, equating to a 10 year period in a medium use washroom.

Finishes:

Aluminium: Powder coated dark grey (RAL 7011) or light grey (RAL 7035).

Door: 0.8mm high pressure laminate from our standard ranges, which include various leading manufacturers.

Divider: 0.8mm high pressure laminate from our standard ranges, which include various leading manufacturers.

Fascia: 0.8mm high pressure laminate from our standard ranges, which include various leading manufacturers.

